

# EASY-KEY KIOSK

## 15.6" Key Dispenser Kiosk

### Scan. Verify. Get Your Key. Go.

- Instant room key dispensing
- NFC Reader, QR Code & Barcode Reader
- Card dispenser for automatic card issuance
- Compact design for reception & self-service areas
- 24/7 automated guest Check-in
- Agile modern hospitality design
- Multilingual & intuitive interface
- Seamless PMS & hotel software integration

Guests simply scan their QR code, verify their reservation, receive their room key, and head directly to their room- quickly, securely, and without queues.



NFC reader



Key Card Dispenser



Smart Design



QR Code Scanner



Wi-Fi, LAN



Mobile & Web Check-in



FOR MORE INFORMATION  
CALL +49 8152 3962500  
OR VISIT US AT [KIOSK.EU](http://KIOSK.EU)



## Guest Journey



### SCAN

Guest scans ID or reservation QR code



### VERIFY

Details are verified instantly through the PMS



### GET KEY

Room card or mobile key is issued quickly



### ENJOY STAY

Guest proceeds directly to their room



#### Compact Design. Maximum Efficiency.

Minimal footprint with powerful functionality



#### Designed for Modern Hospitality

Compact, elegant, and ideal for:

- Boutique hotels
- Serviced apartments
- Self-service reception areas



#### Easy Integration & Setup

Fast setup with seamless hotel system integration.



If you have questions or would like additional information, please contact us at [sales@kiosk.eu](mailto:sales@kiosk.eu) and we can advise about these future-focused options for your specific business goals.

| General Information       |                                                            |
|---------------------------|------------------------------------------------------------|
| Product Dimensions        | 400 x 302 x 509 mm ( W x D x H )                           |
| Max weight                | 15 Kg                                                      |
| Chassis Material          | Chassis: Iron sp15/10                                      |
| Certifications            | CE (TBC, under CE testing)*                                |
| Registered design         | EUIPO                                                      |
| Color                     | Dark gey micaceous iron / Light grey micaceous iron        |
| Surface finishing         | front black micaceius e back light gray sandblasted*       |
| Rated voltage             | 230 V                                                      |
| Power max.                | 200 W                                                      |
| Operating temperature     | 0 to + 40°C* (TBC, under CE testing)*                      |
| Storage temperature       | -20 to +55°C* (TBC, under CE testing)*                     |
| Working umidity Operating | 30% to 90% non-condensing @ 40°C* (TBC, under CE testing)* |
| Working umidity Storage   | 5% to 90% non-condensing @ 40°C* (TBC, under CE testing)*  |
| Display                   |                                                            |
| Video orientation         | Portrait                                                   |
| Display type              | Full HD Touch                                              |
| Resolution                | 15.6 inches                                                |
| Brightness                | 400 cd/m² optional                                         |
| Touch sensor              | 10p PCAP                                                   |
| Contrast                  | 1000:01:00                                                 |
| Viewing angle             | 89° from all sides                                         |
| General Information       |                                                            |
| Product Dimensions        | 400 x 302 x 509 mm ( W x D x H )                           |
| Max weight                | 15 Kg                                                      |
| Chassis Material          | Chassis: Iron sp15/10                                      |
| Certifications            | CE (TBC, under CE testing)*                                |
| Registered design         | EUIPO                                                      |

\*data may change with different configurations.